

Glass melting furnace with high-momentum, oxygen-fired auxiliary burner mounted in the front wall.

Publication number: EP0508139

Publication date: 1992-10-14

Inventor: LAUWERS EDDY J (BE)

Applicant: UNION CARBIDE IND GASES TECH (US)

Classification:

- international: **C03B5/16; C03B5/04; C03B5/20; C03B5/225; C03B5/235; C03B5/00;** (IPC1-7): C03B5/04; C03B5/20; C03B5/235

- European: C03B5/04; C03B5/20B; C03B5/225; C03B5/235B

Application number: EP19920104215 19920311

Priority number(s): US19910684028, 19910411

Also published as:

US5116399 (A1)
JP5116952 (A)
BR9200826 (A)
EP0508139 (B1)


Cited documents:

EP0447300
US3592623
US4473388
WO9012760
US4816056
more >>

[Report a data error here](#)

Abstract of EP0508139

In a glass melting furnace having an upstream melting zone and a downstream fining zone, wherein the glass forming ingredients are introduced to the upstream melting zone via inlet means and the resulting melt therefrom travel along a path from the melting zone to the fining zone, said melt being withdrawn from outlet means which communicate with the fining zone, there is provided at least one high momentum oxygen-fired flame in the vicinity of said outlet means to sweep unmelted glass forming ingredients floating on the surface of the melt away from said vicinity and so prevent said unmelted glass forming ingredients from entering the outlet means whereby the contamination of an outflowing molten glass from said outlet means is avoided or reduced.



Data supplied from the esp@cenet database - Worldwide